



CT SERIES - REEL TRAILER

The CT - Series cable reel trailers from Schutt Industries provides budget-conscious companies a basic, quality reel trailer. The variety of payload, reel diameter and reel width capacities offer exceptional versatility.

Safety features like electric brakes with emergency breakaway system combined with LED lighting, safety chains and chock blocks ensure productivity in a safe environment. Depending upon your cable needs, a gas engine powered hydraulics reel driver and small front reel bar for CATV and telephone reels is available

As with all Schutt Industries products the MMS is exceptionally well crafted. Built on our military grade engineering and manufacturing techniques these units will serve you well for decades of harsh use.

The bottom line is, the Schutt Industries' CT Series trailers increase productivity while keeping expense at a minimum, both now and throughout the life of the trailer.

Contact us today and find out what a Mobile Maintenance Shop can do for your business.

TO ORDER

Phone 715-823-8025

Fax 715-823-8027

sales@schuttindustries.com

www.schuttindustries.com

MODEL NUMBER

CT SERIES

LINK TO PRODUCT



FOR SMARTPHONE USERS:
Use your QRCode scanner app
to read this code and start
experiencing the CT-SERIES.

TO DOWNLOAD A SCANNER APP:

Visit <http://www.upcode.mobi> or search for "QR Code Scanner" where you normally find apps.

TECHNICAL SPECIFICATIONS

PAYLOAD CAPACITIES: 6200 lbs.

REEL DIAMETERS: 36 to 96 inches

REEL WIDTH CAPACITIES: 56 inches

OVERALL LENGTH: 135 inches

OVERALL WIDTH: : 96 inches

LIGHTING: LED PER FMVSS-108

HITCH: ADJUSTABLE TOWING EYE

TRACK WIDTH: 86 inches

GROUND CLEARANCE: 14"

SUSPENSION: Independant Rubber Torsion

AXLE: 8000 LB Torsion Axle

ELECTRICAL SYSTEM: 12V

BRAKES: 12.5 x 3 ELECTRIC

TIRE QUANTITY: 2

TIRE SIZE: LT235/85R16.5

RIM SIZE: 16.5 X 9.75

AVAILABLE OPTIONS:

9" Anti-Backlash Brake, 16" Tensioning Brake, Gasoline Powered Hydraulics for Reel Take-Up and Auxiliary Tool Circuit, Tool Boxes, Load Capacities or 5000, 6500 (shown above) and 8000 lbs, Hot-Dipped Galvanized Finish